

# Ozonette

## WOMAN CARE



CE  
1639



MD

# Technical features

**Operating modes** syringe automatic loading, continuous mode with independent flow adjustment, Insufflation mode (full user control).

**Concentration range** 1 to 80 ug/Nml in steps of 1 ug / Nml.

**ACM concentration measurement** algorithm mathematical calculation.

**N Standardization of the measurement** (regarding pressure and temperature).

**DC dynamic control** for stability and concentration accuracy.

**AD automatic overpressure detection.**

**Output** 3 g/h.

**Optimized oxygen consumption.**

**Compact, high-precision tube**, inert and highly mechanically strength made of the latest generation of materials. Uniform flow distribution.

**High voltage generator™.**

**Ozone removal** by double circuit ozone flow Produced, digitally adjustable from 10 to 50 L/h.

**Operational control** digital touch control.

**Graphic LCD screen.**

**Text-free synoptic interface** (universal and intuitive).

**Weight/Dimensions** 3 kg (6.6 lb) / 25 x 27 x 12cm (9.8 x 10.6 x 4.7 inch).

**Certificates**, CE, RoSH, MDD (IIb class).

**Compatibility with oxygen cylinder** and centralized oxygen supply system.

**Universal external power supply** medical standard (100 to 240 V / 50 to 60 Hz).

**Specific insufflation mode** in vaginal and rectal applications with variable flow adjustment for greater patient comfort and safety with overpressure cut-off under risk analysis.

Ozonette is a compact medical ozone generator that incorporates the latest technological advances. Designed for ozone therapy applications where concentrations must be measured accurately and safely, complying with international standards.

Three modes are available in Ozonette:

- Syringe operation is the most advanced on the market with automatic syringe size detection. The ozone output is done by a double valve system and automatic pressure compensation to avoid unwanted leaks ensuring the user and patient safety.
- Continuous ozone mode operation with variable flow setting and overpressure detection is ideal for local bag therapies in both open and closed circuit, or liquid to be ozonized.
- Insufflation mode operation allows to program concentration and variable flow, activating the ozone production and output controlled by the user, providing the volume data and doses supplied during production.

The compact and high precision tube, inert to the ozone action, and high mechanical strength is manufactured with state-of-the-art materials and consist of a high voltage generator™ by dielectric discharge.

Low consumption, high efficiency and free of annual maintenance.



**SEDECAL S.A.**  
**(Fábrica/Oficinas Centrales)**  
 C/ Pelaya, 9- 13  
 28110 Algete,  
 Madrid (SPAIN)  
 +34 916 280 544  
 O3@sedecal.com  
 www.o3.sedecal.com



**SEDECAL USA**  
 7555 Caldwell Avenue  
 Niles, IL. 60714, USA  
 +847.394.6960  
 O3@sedecal.com  
 www.o3.sedecal.com